Amendments to the Specification:

Please AMEND the paragraph beginning on page 48, line 2 (Abstract of the Disclosure) as follows:

~~This disclosure relates to performing optimal strobe~~ Strobe light emission is ~~control in accordance with the~~ controlled with precision of distance information. ~~This disclosure includes a~~ A photometry unit ~~which~~ measures light reflected by an object to be photographed by preliminary emission in a ~~plurality~~ collection of divided regions[[, an]]. An object distance detection unit[[, a]] detects an object distance. A distance precision determination unit determines a distance precision. ~~(#111 to #117), a~~ A first calculation unit ~~(#121) which~~ calculates a proper photometry level from an object distance. ~~detected by the object distance detection unit, a~~ A second calculation unit ~~(#121) which~~ calculates an identification level for identifying an abnormal reflection region on the basis of the proper photometry level and a distance precision. ~~set in accordance with the determination result of the distance precision determination unit, a~~ A determination unit ~~(#121) which~~ compares the photometry values of the ~~plurality of~~ divided regions with the identification level, thereby determining an abnormal reflection region~~, and a~~. A third calculation unit ~~which~~ calculates the photometry values of reflected object light in the ~~plurality of~~ divided regions from which the abnormal reflection region is excluded.[[,]] ~~wherein strobe~~ Strobe light ~~photographing~~ photography is performed by controlling the main emission amount by the photometry values ~~(#124)~~.